


Haul




Milan



HAUL 40 AC C/W.

Ø40 x 55 mm | H. 160 mm

1 x DOB LED 5W 

500 lumens | 2.700K

| CRI 90


3-step MacAdam

PF. 0,95

Dimmable

Class I: Basic insulation

Finishes

6787  Matt white lacquering
(RAL 9016)

6788  Matt black lacquering
(RAL 9005)

Haul, the distance of light

Cylinder in extruded aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Inner core, with heat sink function and Led housing, injected in aluminium. Injected polycarbonate reflector with high vacuum aluminium finish.

Base where axis is housed for movement, in injected aluminium. Base for fixing to wall or ceiling, injected in zamak. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005).

DOWNLOADS

Catalogue

[Haul](#)

3D Files

[6787/6788](#)

3D Max Files

[6787/6788](#)

Assembly instructions


[6787/6788](#)

Photometric curve

[6787/6788](#)


Economic efficiency index

[6787/6788](#)



HAUL 55 AC C/W.

Ø 40 x 67 mm | H. 198 mm

1 x DOB LED 7W 

665 lumens | 2.700K


| CRI 90

3-step MacAdam

PF. 0,95

Dimmable

Class I: Basic insulation

1 x GU10 Bulb retrofit 

Led 8W Ø50mm

Code 2123


| CRI 90


700 lumens | 2.700K

Dimmable


Class I: Basic insulation

Finishes

6855  Matt white lacquering (RAL 9016)

6856  Matt black lacquering (RAL 9005)

Finishes

6725  Matt white lacquering (RAL 9016)

6726  Matt black lacquering (RAL 9005)

Cylinder in extruded aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Inner core, with heat sink function and Led housing, injected in aluminium. Led " Holder" in polycarbonate injected. Injected polycarbonate reflector, white finishing (MOD. 6855-6856).

Base where axis is housed for movement, in injected aluminium. Base for fixing to wall or ceiling, injected in zamak. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Polycarbonate injected decorative ring. Assembly by pressure. Finishing in white, black and translucent.

DOWNLOADS

Catalogue

[Haul](#)

3D Files

[6855/6856](#)

[6725/6726](#)

3D Max Files

[6855/6856](#)

[6725/6726](#)

Assembly instructions

[6855/6856](#)

[6725/6726](#)

Photometric curve

[6855/6856](#)

[6725/6726](#)

Economic efficiency index

[6855/6856](#)

[6725/6726](#)