

Half



Milan






MLN HALF

Ø160 mm | H Min. 190 mm
/ H Max. 1.698 mm
1x E27 Spherical bulb retrofit
led 5,5 W
396 lumen | 2.700 K
Dimmable
☑ Class II: Basic insulate plus reinforced insulation

Finishes

6742 ● NE 6744 ● OG
6743 ● VI



4763 ● NE
Marble



4769 ● FR
Ash wood




MLN HALF

Ø250 mm | H Max. 1.600 mm
1x E27 Standard bulb
led 9 W
888 lumen | 2.700 K
Dimmable
☑ Class II: Basic insulate plus reinforced insulation

Finishes

6745 ● NE 6747 ● OG
6746 ● VI



4764 ● NE
Marble



4770 ● FR
Ash wood




MLN HALF

Ø350 mm | H Max. 1.700 mm
1x E27 Spherical bulb retrofit
led 12 W
1.000 lumens | 2.700 K
Dimmable
☑ Class II: Basic insulate plus reinforced insulation

Finishes

6748 ● NE 6750 ● OG
6749 ● VI



4765 ● NE
Marble



4771 ● FR
Ash wood



DOWNLOADS

Catalogue

3D Files

6742+4763	6745+4770
6743+4763	6746+4770
6744+4763	6747+4770
6742+4769	6748+4765
6743+4769	6749+4765
6744+4769	6750+4765
6745+4764	6748+4771
6746+4764	6749+4771
6747+4764	6750+4771

3D Max Files

6742+4763	6745+4770
6743+4763	6746+4770
6744+4763	6747+4770
6742+4769	6748+4765
6743+4769	6749+4765
6744+4769	6750+4765
6745+4764	6748+4771
6746+4764	6749+4771
6747+4764	6750+4771

Assembly instructions

Photometric curve

Economic efficiency index

6742	6747
6743	6748
6744	6749
6745	6750
6746	

Sphere of 160, 250 or 350 mm diameter, formed by two hemispheres: bases stamped in steel with finishes in lacquered matte black (RAL 9005), lacquered mink (NCS S 2005-Y10R) and lacquered olive grey (RAL 6006), an diffusing screen made of satin opal acid-etched blown glass.

Black electrical cable, 3 meters long.

Marble base has a neodymium magnet that helps to fit the metallic part of the sphere.